63ZYT Series

General Specification

Voltage Range 电压范围	12 & 24V dc (240V also available)
Power Output Range 输出功率范围	40 ~ 100 W
Speed Range 转速范围	up to 10,000 rpm
Operational Temperature 操作温度	–20℃ ~ +40℃
Insulation Class 绝缘等级	F (consult us for class B)
Bear Type 轴承类型	High quality ball bearings
Housing Type 机壳种类	Closed (ventilated also available)



Performance Data

Part Number 型号	Units	63ZYT95–12V	63ZYT95–24V	63ZYT125–12V	63ZYT125–24V
Voltage 电压	V	12	24	12	24
Rated Power 额定功率	W	44.5	32.7	93.3	94.7
Rated Speed 额定转速	rpm	3100	1840	3000	3300
Rated Torque 额定扭矩	mNm	137	170	270	270
Rated Current 额定电流	A	5.2	2	10.5	5.0
No load Speed 空载转速	rpm	3600	2100	3200	3650
Length 长度	mm	95	95	125	125

Dimensions in mm



73ZYT Series

General Specification

Voltage Range 电压范围	12 & 24V dc (48V also available)
Power Output Range 输出功率范围	90 ~ 150 W
Speed Range 转速范围	up to 9,000 rpm
Operational Temperature 操作温度	–20℃ ~ +40℃
Insulation Class 绝缘等级	F (consult us for class B)
Bear Type 轴承类型	High quality ball bearings
Housing Type 机壳种类	Closed (ventilated also available)



Performance Data

Part Number 型号	Units	73ZYT145–12V	73ZYT155–12V	73ZYT127–24V	73ZYT165–24V
Voltage 电压	V	12	12	24	24
Rated Power 额定功率	W	120	134	100	170
Rated Speed 额定转速	rpm	3700	3200	4700	3200
Rated Torque 额定扭矩	mNm	300	400	200	500
Rated Current 额定电流	A	15	13	5.5	9
No load Speed 空载转速	rpm	4200	3600	5200	3600
Length 长度	mm	145	155	127	165

Dimensions in mm